

Colour	Product	Vetrosa	UV-curing	high firing temperatures, approx. 900-1000°C/1650-1830° F)	Notes	
light yellow	GZ 5324				lemon yellow firing result	new!
yellow	GGP 2450				also suitable for fast firing, wide firing range	
yellow	GGP 2519/UV		●		-	
yellow	GGP 2603				normal firing, well-tried standard preparation, excellent printing properties, excellent mechanical and chemical resistance	
yellow	GGP 2456		●		special product for the decoration of tiles, excellent printing properties, excellent mechanical and chemical resistance	
yellow	GGP 2608				normal firing, well-tried standard preparation, excellent printing properties, excellent mechanical and chemical resistance	
yellow	GGP 2457				normal firing, well-priced special preparation for tiles, wide firing range, excellent printing properties, excellent mechanical and chemical resistance	
yellow	GGP 2621				most reasonable preparation	
yellow	GGP 2573				wide firing range up to 920°C/1688°F, excellent printing properties, excellent mechanical and chemical resistance	
yellow	GGP 2346				wide firing range up to 920°C/1688°F, excellent printing properties, excellent mechanical and chemical resistance	
yellow	TGG0158A				-	new!
reddish yellow	GG 5310				excellent mechanical resistance, firing range up to 940°C/1720°F	new!
reddish yellow	TGG0157A10				-	new!
reddish yellow	GGP 2385/HT		●		high temperature bright gold paste, for soft tile glazes, can be fired next to vetrosa in one fire	
reddish yellow	GGP 2617		●		also suitable for fast firing, wide firing range up to 1000°C/1830°F, excellent mechanical and chemical resistance	